



Français
 1 of 1

&DOC=04/082989&TYPE=A2" TARGET="pages">Images

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(11) WO 2004/082989

(13) A2

(21) PCT/DE2004/000540

(22) 17 March 2004 (17.03.2004)

(25) German

(26) German

(30) 103 11 861.6

17 March 2003

DE

(17.03.2003)

(30) 203 20 371.2

10 June 2003

DE

(10.06.2003)

(43) 30 September 2004 (30.09.2004)

(51)⁷ B60N 2/56

(54) DEVICE FOR RECEIVING FUNCTIONAL ELEMENTS

(71) W.E.T. AUTOMOTIVE SYSTEMS AG [DE/DE]; Rudolf-Diesel-Strasse 12, 85235 Odelzhausen (DE).

(72)

(75) STÖWE, Stefan [DE/DE]; Schillerstrasse 6, 86415 Mering (DE).

(81) AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW


(84) ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG, BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

For information on time limits for entry into the national phase please click here

Published


-- without international search report and to be republished upon receipt of that report

(57) The invention relates to a device (2) for receiving functional elements in zones of a vehicle interior that are at least temporarily subjected to mechanical forces. Said device



comprises a base layer (8), an intermediate layer (10) and a covering layer (12), said layers (8, 10, 12) at least partially overlapping one another. The intermediate layer (10) comprises at least one support element (14) for transmitting mechanical loads between the base layer (8) and the covering layer (12), said layer being configured from a solid but flexible material. According to the invention, additional, in particular, electric functional elements (18) are located in addition to the support element (14) in the space (16) between the base layer (8), the covering layer (12) and said support element (14).



Français 
1 of 1